


SP II type



Power Line Special-Type SPD



Function

Surge event display, Power quality analysis display (over voltage/under voltage events)

Rated voltage (3-phase: R-S, S-T, R-T/single-phase: L-N, L-G N-G), Individual leakage current display

External display connected (RS485 data transmitted) / RS485, Ethernet, Mobile app (Bluetooth)

Specification

Product Features

Voltage	AC 460V/440V/380V/220V/110V DC 600V/440V/380V/200V	CE certificate, KS certificate, Patents High-performance, High-capacity SPD(Total 800, 500, 400, 360, 320, 240kA) Full mode protection (Line-Neutral, Line-Ground, Line-Line) Performance in compliance with KS C IEC 61643-11 Surge counter, Over voltage counter, Under voltage counter memory (non-volatile) Surge protector diagnosis (Leakage current measurement by phase, Failure indicator, Buzzer) Dual safety design (current & thermal fuse) Hourmeter (1/10 h) recording and temperature measurement Rated voltage measurement (3-phase: R-S, S-T, R-T/single-phase: L-N, L-G N-G) Communication function (RS485, Ethernet, Bluetooth) Surge Protector information Display (PD Power Meter) (optional) Aluminum case for proven safety against surge protector failure
Type	3-Phase 4-Wire/3-Phase 3-Wire Single-Phase 2-Wire (Serial/Parallel)	
Capacity	800KA/500KA/400KA/360KA/ 320KA/240KA Total	

Class I Surge Protector

SPD Class **Class I Surge Protector (Class I SPD)**
Model **KOP-A-20KI-KS [Single-Phase 2-Wire, Parallel]**
SPD Type Special 1, 2
Application [*LPZ0, *LPZ1] Power and earthing line lightning, Switching surge protection
Application Field Incoming panel, Distribution board, 3-phase UPS, Inverter, Motor driver, Actuator power and other 3-phase power devices Electrical property



Power Line SPD

Signal/Telecom SPD

LAN/Coaxial SPD

Power+LAN Integrated Surge Protector

Hourmeter

Electrical property

Rated voltage	Un	220~260V AC [Ph-N]
Rated current		N/A
Power system configuration		Single-Phase 2-Wire, Parallel connection
Max Continuous Operating Voltage (MCOV)	Uc	275V AC [L-N], 275V AC [N-PE]
Rated frequency	f	50 / 60 Hz
Leakage current (@Uc)	IL	Less than 1 mA
Insulation resistance (@500V DC)	RIN	Above 10 MΩ

Protection property

Protection mode		L-N	N-G	L-G
Voltage protection level [KS / CE Class 1 test] <small>(Imp 20kA @ 10/350μs) – IEC 61643-11</small>	Up	≤ 2,500V	≤ 2,500V	≤ 2,500V
Max current capacity <small>(@Current 8/20μs) [Total : 250kA]</small>		200kA	50kA	0kA
Impulse discharge current <small>(@Current 10/350μs) – IEC 61643-11</small>	Iimp	20kA	20kA	0kA
Nominal discharge current <small>(@Current 8/20μs)</small>	In	40kA	40kA	0kA
Response time (@10kV/μs)	ta	Less than 5 ns		
Power noise filter (Frequency band and Damping rate)	Fc	N/A		

Features

	Operation status	Run = green lamp / Fault = red lamp [L-N]
Special I . II	Safety	Dual safety design [current & thermal fuse]
	Surge information display	Surge counter (Back light LCD)
	Alarm	Fault buzzer
	Measurement	Rated voltage display, Individual leakage current display
Special II	Condition record display	Surge event memory, Over voltage event memory, Under voltage event memory (Line to Line)
	Communication function	RS 485, Ethernet Modbus RTU Protocol (ASCII not Supported), APP(Bluetooth)
	Measurement	Temperature measurement and display, Cumulative operating time display

Mechanical property

Protection rating level	IP20 (@IEC 60529), NEMA1
Operating temperature and humidity	-40~ 90°C, ≤ 95%
Terminal	101A IEC type [Awg 4~22 / 0.5~16mm]
Size	[SP-1/SP-2] (W)140 x (L)226 x (H)90 mm cf. p37 A-3
Installation	Bolt mounting
Weight	Less than 2kg

Test standard & Reference

- IEC 61643-11 [2017] Performance and Test Criteria for Power Line Surge Protector
- IEC 61643-12 [2017] Lightning Protection Zone 1,2,3
- IEC 62305-1,2,3,4 [2017]
- ANSI/IEEE Std C62.45 [2002] Guide to Surge Test for Low-pressure Device
- ANSI/IEEE Std C62.41 [2002] Category A, B, C
- IEEE Std C62.34 [2017] Power line surge protector performance standard
- IEEE Std C62.62 [2018] Power line surge protector standard test specification

*LPZ : Lightning Protection Zone(lightning protection area)

Size

Power Line Class I SPD Special I , II , III type



Model List A-2
(W)140 x (L)276 x (H)90

3-phase

- KOP-B-20KI-KS (SP-I, II)
- KOP-B-500K-KS (SP-III)



Model List A-3
(W)140 x (L)226 x (H)90

Single-phase

- KOP-A-20KI-KS (SP-I, II)

[Unit : mm]

