

Power Line Special-Type SPD



RS485



SPD Power Meter

Function

Surge Counter

Rated voltage (3-phase: R-S, S-T, R-T/single-phase: L-N, L-G N-G), Individual leakage current display

External display connected (RS485 data transmitted)

Specification

Product Features

| | | |
|-----------------|--|---|
| Voltage | AC 460V/440V/380V/220V/110V DC 600V/440V/380V/200V | CE certificate, KS certificate, Patents High-performance, High-capacity SPD (Total 800, 500, 400, 360, 320, 240kA) Full mode protection (Line-Neutral, Line-Ground, Line-Line) Performance in compliance with KS C IEC 61643-11 |
| Type | 3-Phase 4-Wire/3-Phase 3-Wire Single-Phase 2-Wire (Serial/Parallel) | Surge counter memory (non-volatile) Surge protector diagnosis (Leakage current measurement by phase, Failure indicator, Buzzer) Dual safety design (current & thermal fuse) |
| Capacity | 800KA/500KA/400KA/ 360KA/320KA/240KA Total | Rated voltage measurement (3-phase: R-S, S-T, R-T/single-phase: L-N, L-G N-G) Communication function Surge Protector information Display (PD Power Meter) (optional) Aluminum case for proven safety against surge protector failure |

Class III Surge Protector



| | |
|-------------------|---|
| SPD Class | Class III Surge Protector (Class III SPD) |
| Model | KOP-B-400K [3-Phase 4-Wire, Parallel] |
| SPD Type | Special 1, 2 |
| Application | [*LPZ2, *LPZ3] Power and earthing line lightning, Switching surge protection |
| Application Field | Incoming panel, Distribution board, 3-phase UPS, Inverter, Motor driver, Actuator, and other 3 phase power3-phase power devices |

Electrical property

| | | |
|---|-----|---|
| Rated voltage | Un | 380~460V AC [Ph-Ph], 220~260V AC [Ph-N] |
| Rated current | | N/A |
| Power system configuration | | 3-Phase 4-Wire, Parallel connection |
| Max Continuous Operating Voltage (MCOV) | Uc | 480V AC [Ph-Ph], 275V AC [N-G] |
| Rated frequency | f | 50 / 60 Hz |
| Leakage current (@Uc) | IL | Less than 1 mA |
| Insulation resistance (@500V DC) | RIN | Above 10 MΩ |

Protection property

| Protection mode | | L1-N | L2-N | L3-N | N-G |
|--|----|----------------|----------|----------|----------|
| Voltage protection level [CE Class 3 test] <small>(@20kV/10kA Voltage 1,2/50 μs, Current 8/20μs) - IEC 61643-11</small> | Up | ≤ 2,500V | ≤ 2,500V | ≤ 2,500V | ≤ 1,000V |
| Max current capacity <small>(@Current 8/20μs) [Total : 400kA]</small> | | 100kA | 100kA | 100kA | 100kA |
| Response time (@10kV/μs) | ta | Less than 5 ns | | | |
| Power noise filter (Frequency band and Damping rate) | Fc | N/A | | | |

Features

| | Operation status | Run = green lamp / Fault = red lamp [L1-N, L2-N, L3-N] |
|------------------------|---------------------------|--|
| Special I . II | Safety | Dual safety design [current & thermal fuse] |
| | Surge information display | Surge counter (Back light LCD) |
| | Alarm | Fault buzzer |
| | Measurement | Rated voltage display, Individual leakage current display |
| | Special II | Condition record display |
| Communication function | | RS 485, Ethernet Modbus RTU Protocol (ASCII not Supported), APP(Bluetooth) |
| Measurement | | Temperature measurement and display, Cumulative operating time display |

Mechanical property

| | |
|------------------------------------|---|
| Protection rating level | IP20 (@IEC 60529), NEMA1 |
| Operating temperature and humidity | -40~ 90°C, ≤ 95% |
| Terminal | 57A Euro type [Awg 8~22 / 0.5~10mm] |
| Size | [SP-1] (W)140 x (L)190 x (H)70 mm cf. 39 C-1 [SP-2] (W)140 x (L)190 x (H)90 mm C-2 |
| Installation | Bolt mounting |
| Weight | Less than 1,5kg |

Test standard & Reference

- IEC 61643-11 [2017] Performance and Test Criteria for Power Line Surge Protector
- IEC 61643-12 [2017] Lightning Protection Zone 1,2,3
- IEC 62305-1,2,3,4 [2017]
- ANSI/IEEE Std C62.45 [2002] Guide to Surge Test for Low-pressure Device
- ANSI/IEEE Std C62.41 [2002] Category A, B, C
- IEEE Std C62.34 [2017] Power line surge protector performance standard
- IEEE Std C62.62 [2018] Power line surge protector standard test specification

*LPZ : Lightning Protection Zone(lightning protection area)

Power Line SPD

Signal/Telecom SPD

LAN/ Coaxial SPD

Power+LAN Integrated Surge Protector

Hourmeter

Size

Power Line Class III SPD Special I , II Type



Model List C-1
(W)140 x (L)190 x (H)70

Single-phase

- KOP-A-240K <SP-I >
- KOP-A-320K <SP-I >
- KOP-A-360K <SP-I >

3-phase

- KOP-B-360K <SP-I >
- KOP-B-400K <SP-I >



Model List C-2
(W)140 x (L)190 x (H)90

Single-phase

- KOP-A-240K <SP-II >
- KOP-A-320K <SP-II >
- KOP-A-360K <SP-II >

3-phase

- KOP-B-360K <SP-II >
- KOP-B-400K <SP-II >

[Unit : mm]

