

Coaxial BNC type



Coaxial BNC type



Specification

Product Features

Voltage	DC 24V / 5V	<p>CE-certified, Patented</p> <p>Performance in compliance with IEC standard [When 20 kV/10 kA (Voltage 1.2/50 μs, Current 8/20 μs) is applied, Within 150 V]</p> <p>High surge capacity - 50 kA in all, the highest in the world</p> <p>Reverse surge protection - first in the world</p> <p>BNC Connector</p> <p>Aluminum case</p>
Type	Coaxial (Serial)	
Capacity	50kA - total / 25kA - mode	

Application

CCTV/DVR Video Line, Ultrasonic Flowmeter Line, Wireless Antenna, etc.

Coaxial BNC type



BNC type

Model KOX-A-24DC
Application Antenna, RF Communication, Cable TV Protection
Application Field CCTV, F-met, Cable TV, etc. - industry field



Electrical property

Rated voltage	Un	24V DC
Max Continuous Operating Voltage (MCOV)	Uc	36V DC
Nominal current		300 mA
Insulation resistance (@DC)	RIN	Above 20 MΩ
DC Loop resistance	R	Less than 50 Ω/1wire

Protection property

Protection mode (Full mode protection)		L1-L2(G)
Voltage protection level (Category C2) (@20kV/10kA Voltage 1,2/50μs, Current 8/20μs) – IEC 61643-21	Up	≤ 150V
Maximum discharge current DM:0kA, CM:50kA (@Current 8/20μs)	Imax	50kA
Nominal discharge current (@Current 8/20μs)	In	20kA
Response time (@10kV/μs)	ta	Less than 5 ns

Features

Capacitance (@1MHz, 1Vrms)	C	1.5nF
Insertion loss (@3dB)	BW	DC~10MHz

Mechanical property

Protection rating level	IP20 (@IEC 60529), NEMA1
Operating temperature	-40 ~ 90°C
Operating humidity	Less than 95%
Size	(W)42 x (L)118 x (H)30 mm cf. p72
Installation	Bolt mounting
Weight	Less than 250g

Test standard & Reference

UL 497B

IEC 61643-21 [2015] Category A, B, C Performance and Test Criteria for Data/Telecom/Signal Line Surge Protector

IEC 62305-1,2,3,4 [2017]

Performance and Test Criteria for Circuit Surge Protector

ANSI/IEEE Std C62.64 [2009] Data/Telecom/Signal Line Surge Protector performance standard

IEEE Std c62.36 [2016] Data/Telecom/Signal Surge Line Surge Protector standard test specification

*DM(Differential Mode[Differential Mode])=NM(Normal Mode[Normal Mode])=Symmetrical Mode

*CM(Common Mode[Common Mode])=LM(Longitudinal Mode[Longitudinal Mode])=Asymmetrical Mode

Power Line SPD

Signal/Telecom SPD

LAN/ Coaxial SPD

Power+LAN Integrated Surge Protector

Hourmeter

Size

Coaxial Line BNC type



Model List

(W)42 x (L)118 x (H)30

- KOX-A-24DC
- KOX-A-48DC

[Unit : mm]

